

## 1A, 50V - 1000V Surface Mount Rectifier

### FEATURES

- AEC-Q101 qualified
- Glass passivated chip junction
- Ideal for automated placement
- Low forward voltage drop
- Moisture sensitivity level: level 1, per J-STD-020
- RoHS Compliant
- Halogen-free according to IEC 61249-2-21

### APPLICATIONS

- DC to DC converter
- Automotive application
- Car lighting
- Snubber
- General purpose

### MECHANICAL DATA

- Case: DO-214AC (SMA)
- Molding compound meets UL 94V-0 flammability rating
- Terminal: Matte tin plated leads, solderable per J-STD-002
- Meet JESD 201 class 2 whisker test
- Polarity: Indicated by cathode band
- Weight: 0.060g (approximately)

KEY PARAMETERS		
PARAMETER	VALUE	UNIT
$I_F$	1	A
$V_{RRM}$	50 - 1000	V
$I_{FSM}$	30, 40	A
$T_{JMAX}$	175	°C
Package	DO-214AC (SMA)	
Configuration	Single die	



**DO-214AC (SMA)**



ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ unless otherwise noted)										
PARAMETER	SYMBOL	S1 AH	S1 BH	S1 DH	S1 GH	S1 JH	S1 KH	S1 MH	UNIT	
Marking code on the device		S1A	S1B	S1D	S1G	S1J	S1K	S1M		
Repetitive peak reverse voltage	$V_{RRM}$	50	100	200	400	600	800	1000	V	
Reverse voltage, total rms value	$V_{R(RMS)}$	35	70	140	280	420	560	700	V	
Forward current	$I_F$	1								A
Peak forward surge current, 8.3ms single half sine wave superimposed on rated load	$I_{FSM}$	40						30		A
Non-repetitive peak reverse avalanche energy, $I_{AS} = 1\text{A}$ , $L = 10\text{mH}$	$E_{RSM}$	5								mJ
Junction temperature	$T_J$	- 55 to +175								°C
Storage temperature	$T_{STG}$	- 55 to +175								°C

<b>THERMAL PERFORMANCE</b>					
PARAMETER		SYMBOL	TYP		UNIT
Junction-to-lead thermal resistance	S1AH S1BH S1DH S1GH S1JH	$R_{\theta JL}$	27		$^{\circ}C/W$
	S1KH S1MH		30		$^{\circ}C/W$
Junction-to-ambient thermal resistance	S1AH S1BH S1DH S1GH S1JH	$R_{\theta JA}$	75		$^{\circ}C/W$
	S1KH S1MH		85		$^{\circ}C/W$

<b>ELECTRICAL SPECIFICATIONS</b> ( $T_A = 25^{\circ}C$ unless otherwise noted)					
PARAMETER	CONDITIONS	SYMBOL	TYP	MAX	UNIT
Forward voltage <sup>(1)</sup>	$I_F = 1A, T_J = 25^{\circ}C$	$V_F$	-	1.1	V
Reverse current @ rated $V_R$ <sup>(2)</sup>	$T_J = 25^{\circ}C$	$I_R$	-	1	$\mu A$
	$T_J = 125^{\circ}C$		-	50	$\mu A$
Junction capacitance	$1MHz, V_R = 4.0V$	$C_J$	12	-	pF
Reverse recovery time	$I_F = 0.5A, I_R = 1.0A, I_{rr} = 0.25A$	$t_{rr}$	1500	-	ns

**Notes:**

1. Pulse test with  $PW = 0.3ms$
2. Pulse test with  $PW = 30ms$

<b>ORDERING INFORMATION</b>		
ORDERING CODE <sup>(1)</sup>	PACKAGE	PACKING
S1xH	DO-214AC (SMA)	7,500 / Tape & Reel


**Notes:**

1. "x" defines voltage from 50V(S1AH) to 1000V(S1MH)


**CHARACTERISTICS CURVES**

( $T_A = 25^\circ\text{C}$  unless otherwise noted)


**Fig.1 Forward Current Derating Curve**




**Fig.2 Typical Junction Capacitance**




**Fig.3 Typical Reverse Characteristics**



**Fig.4 Typical Forward Characteristics**




**Fig.5 Maximum Non-Repetitive Forward Surge Current**



**CHARACTERISTICS CURVES**


( $T_A = 25^\circ\text{C}$  unless otherwise noted)

**Fig.6 Reverse Recovery Time Characteristic And Test Circuit Diagram**



**PACKAGE OUTLINE DIMENSIONS**

DO-214AC (SMA)



DIM.	Unit (mm)		Unit (inch)	
	Min.	Max.	Min.	Max.
A	1.99	2.50	0.078	0.098
A1	0.10	0.20	0.004	0.008
b	1.27	1.58	0.050	0.062
c	0.15	0.31	0.006	0.012
D	2.29	2.83	0.090	0.111
E	4.95	5.33	0.195	0.210
E1	4.06	4.60	0.160	0.181
L	0.90	1.41	0.035	0.056

**SUGGESTED PAD LAYOUT**



Symbol	Unit (mm)	Unit (inch)
A	1.68	0.066
B	1.52	0.060
C	3.93	0.155
D	2.41	0.095
E	5.45	0.215

**MARKING DIAGRAM**



- P/N = Marking Code
- G = Green Compound
- YW = Date Code
- F = Factory Code

## **Notice**

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.